



USB-C to HDMI Converter with Power Delivery Port

4K@60Hz Resolution, Power Delivery up to 60 W (20 V / 3 A), Black

Part No.: [153416](#)

EAN-13: 0766623153416 | UPC: 766623153416

Our USB-C to HDMI Converter with Power Delivery (PD) Port: UHD HDMI from your device's USB-C port and power for all devices

The Manhattan USB-C to HDMI Converter with PD Port lets you easily show content from your USB-C-equipped device on an existing HDMI display, monitor or projector. This converter is easy and quick to install — no settings or adjustments required. It is a compact yet powerful solution that helps avoid extra cables, tangles and clutter to keep workspaces neat and tidy.

USB-C Power Delivery

The included USB-C PD port gives up to 60 W (20 V / 3 A) to all devices in your setup. Connecting the upstream device's cable and adapter supplies power to the upstream device and boosts the 4K signal to your display for the perfect picture. The PD function also provides faster charging than standard chargers since it finds out the power needs of compatible devices and supplies it at the quickest and safest rate.

Features:

- Supports resolutions up to 4K@60Hz following HDMI 2.0 standards
- Supports Power Delivery (PD) up to 60 W (20 V / 3 A)
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Thunderbolt 3 compatible

- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play; requires no external power supply
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- DP 1.2 Alternate Mode
- PD 3.0
- HDMI
- HDCP 2.2
- CE
- FCC
- RoHS2
- WEEE

Connections

- USB type C, 24-pin, male
- HDMI, 19-pin, female
- Power Delivery USB-C port

Video Resolutions

- 4K@60Hz
- 4K@30Hz
- 1080p
- 720p
- 1024x768
- 800x600
- 640x480

Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Dimensions: 60 x 40 x 16 mm (2.36 x 1.57 x 0.63 in.)
- Cable length: 19.5 cm (7.67 in.)
- Weight: 31.76 g (1.12 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: 0 – 50°C (32 – 122°F)
- Storage Temperature: -40 – 85°C (-40 – 185°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10
- Mac 9.x/10.x or above
- Android

Package Contents

- USB-C to HDMI Converter with Power Delivery Port
- Quick Instruction Guide

This product is part of a group; the complete list of variations follows:

- #153690 - USB-A to HDMI
- #151788 - USB-C to HDMI, 4K@30Hz
- #153416 - USB-C to HDMI, 4K@60Hz, PD Port



