



4-Port USB 3.0 Type-A Hub

USB-A Male to Four USB-A Females, 5 Gbps SuperSpeed USB (USB 3.2 Gen 1), Bus Powered, Black

Part No.: [164900](#)

EAN-13: 0766623164900 | UPC: 766623164900

More ways to connect your USB-A devices

The Manhattan 4-Port USB 3.0 Type-A Hub turns one of your device's USB ports into four so you can easily connect a keyboard, mouse, flash drive and more. Devices that fit the SuperSpeed (USB 3.2 Gen 1, formerly known as USB 3.0) spec can reach transfer speeds up to 5 Gbps for external storage, printing and more. The hub's SuperSpeed ports are backward compatible to run older USB versions, too. Plus, you can charge your phone or tablet since the hub supplies up to 5 V / 1 A of power.

Connectivity you can take with you

This hub's durable case, compact size and bus power mean greater portability for you when you have to pack up and go. You don't have to worry about an additional power supply to carry, which makes the hub an ideal travel companion. Simply unplug the hub from your upstream device, disconnect your peripherals and put what you need in your laptop bag to be on your way. Its Plug-and-Play installation and hot-swap ability means you are able to get set up and working — or playing— in no time.

Features:

- Adds four SuperSpeed USB ports to a USB device for better access to your keyboard, mouse, flash drive, smartphone, tablet and more
- Supports SuperSpeed data transmission up to 5 Gbps
- Bus powered; no external power supply needed
- Includes an LED power indicator
- Plug-and-Play installation; hot swappable
- Windows and Mac compatible

- Three-year warranty

Specifications:

Standards and Certifications

- USB 3.2 Gen 1 (USB 3.0)
- FCC
- CE
- RoHS
- REACH
- UKCA

General

- Data transfer speeds: 5 Gbps
- One USB-A male
- Four USB-A female
- Up to 1 A total power output
- Bus powered

Connections

- One USB-A, 4-pin, male
- Four USB-A, 4-pin, female

Physical

- 24-AWG cable gauge
- Cable Length (including connector): 13.5 cm (5.31 in.)
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm
- Housing: ABS plastic
- Dimensions: 107 x 30 x 11 mm (4.21 x 1.18 x 0.43 in.)
- Weight: 39 g (1.1 oz.)
- Shielded

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 5 – 90%

System Requirements

- Windows XP/Vista/7/8.1/10/11 or Linux or Mac 9.x/10.x or above

Package Contents

- 4-Port USB 3.0 Type-A Hub
- Quick Instruction Guide

