



EXT-RS232

Bidirectional RS-232 over Twisted Pair
Extender



The EXT-RS232 is a twisted pair transmitter and receiver for RS-232 signals. It converts RS-232 signals into a twisted pair signal, which is then converted back to a RS-232 signal

FEATURES

- System Range - 1000m (3300ft) over Kramer shielded cables
- Transmission Rate - 57.6kbps
- Full-Duplex Data Communication
- Compatible with all RS-232 Protocols



TECHNICAL SPECIFICATIONS

INPUTS:	RS-232 on a 9-pin D-sub F connector (local unit), CAT 5 on an RJ-45 connector (remote unit)
OUTPUTS:	CAT 5 on an RJ-45 connector (local unit), RS-232 on a 9-pin D-sub M connector (remote unit)
SYSTEM CABLE:	CAT 5 UTP/FTP 2x4x24AWG solid wire cable
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	80% RHL non-condensing
INCLUDED ACCESSORIES:	12V DC, 1A power supply
Product Dimensions	4.50cm x 7.40cm x 2.30cm (1.77" x 2.91" x 0.91") W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15") W, D, H
Shipping Weight	0.4kg (0.8lbs) approx