



kramer

VM-212DT

2x1:2 4K60 4:2:0 HDMI & Extended-Reach
HDBaseT with Ethernet, RS-232, IR &
Stereo Audio Switchable DA

| HDMI | Ethernet - RJ-45 | HDCP Compliant
| HDBaseT | 4K/60 UHD (4:2:0)



The VM-212DT is 4K@60Hz (4:2:0) HDMI & extended-reach HDBaseT DA for HDMI and HDBaseT signals. It reclocks and equalizes the signal and distributes it to two identical HDBaseT outputs and a looping HDMI output. It supports resolutions up to 4K@60Hz (4:2:0). This product offers the versatility of control options and audio de-embedding

FEATURES

- Max. Resolution - 4K@60Hz (4:2:0)
- Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel)
- HDTV Compatible
- HDCP Compliant - Works with sources that support HDCP repeater mode
- HDMI Support - Deep Color, x.v.Color™ and 3D
- Automatic Live Input Detection - Based on video clock presence
- Automatic Analog Audio Detection & De-embedding
- Looping HDMI Output - Allow monitoring and cascading to additional DAs
- EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems
- System Range - Up to 130m (430ft) at normal mode (2K), up to 100m at normal mode (4K); up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-UNIKAT cables
- Data Equalization and Reclocking
- Support for Digital Audio Formats
- Lockable EDID and Default EDID - For fast and efficient connection of the unit
- Support for EDID Designer



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|--|
| INPUTS: | 1 HDMI connector, 1 HDBT twisted pair on an RJ-45 connector |
| OUTPUTS: | 1 HDMI connector, 2 HDBT twisted pair on RJ-45 connectors |
| MAX. DATA RATE: | 10.2Gbps (3.4Gbps per graphic channel, HDMI) |
| COMPLIANCE WITH HDMI STANDARDS: | Supports HDMI and HDCP |
| CONTROLS: | Input select button, EDID select button, panel lock button, RS-232, local and remote IR controls |
| INDICATOR LEDS: | IR communication, Power, IN 1 HDMI, IN 2 HDBT, OUTPUT 1 and 2, EDID TYPE Default, External, Output |
| POWER CONSUMPTION: | 100–240V AC 50/60Hz 16VA |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| COOLING: | Forced air, fan |
| ENCLOSURE TYPE: | Aluminum |
| RACK MOUNT: | With included rack "ears" |
| VIBRATION: | ISTA 1A in carton (International Safe Transit Association) |
| SAFETY REGULATORY COMPLIANCE: | CE |
| ENVIRONMENTAL REGULATORY COMPLIANCE: | Complies with appropriate requirements of RoHs and WEEE |
| INCLUDED ACCESSORIES: | Power cord, rack "ears" |
| Product Dimensions | 19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H |
| Product Weight | 1.3kg (3.0lbs) approx |
| Shipping Dimensions | 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H |
| Shipping Weight | 2.1kg (4.6lbs) approx |



