



## VA-8xl

8-Channel Balanced Stereo Volume  
Controller

---



The VA-8xl is a high-performance 8 channel-balanced stereo input volume controller for balanced audio signals on terminal block connectors. The volume of each L & R stereo channel can be adjusted independently of the other stereo channel

## FEATURES

---

Input - 8 balanced stereo

Output - 8 balanced stereo

S/N Ratio - >90dB

Volume - -95dB to +31dB in 0.5dB steps; L & R channels may be controlled separately or together

Control - Front panel, RS-232 and RS-485

Worldwide Power Supply - 100-240V AC

Standard 19" Rack Mount Size - 1U



## TECHNICAL SPECIFICATIONS

---

INPUT:	8 balanced stereo audio +4dBu/30k $\Omega$ on detachable terminal blocks
OUTPUT:	8 balanced stereo audio +4dBu/50 $\Omega$ on detachable terminal blocks
GAIN:	-95dB to +31dB
MAX. OUTPUT LEVEL:	>20dBu balanced (THD+N <0.01)
BANDWIDTH ( - 3dB):	20Hz to 40kHz
NOISE FLOOR:	<90dB (gain 0dB)
THD + NOISE:	0.006% @4dBu 1kHz
CONTROL:	Front pushbuttons, RS-232, and RS-485
INDICATORS:	Gain in dB for left and right channels
POWER CONSUMPTION:	100-240V, 13VA
INCLUDED ACCESSORIES:	Power cord, null-modem adapter, Windows®-based Kramer control software
Product Dimensions	19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H
Product Weight	2.7kg (6.0lbs) approx
Shipping Dimensions	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H
Shipping Weight	3.5kg (7.8lbs) approx

