



VM-3AN

1:3 Balanced Stereo Audio Distribution
Amplifier



The VM-3AN is a high-performance distribution amplifier for balanced stereo audio signals. The unit takes one stereo input and distributes the signal to three identical outputs

FEATURES

S/N Ratio - 90dB

L & R Level (Gain) Controls



TECHNICAL SPECIFICATIONS

INPUT:	1 balanced stereo audio on a 5-pin terminal block
OUTPUTS:	3 balanced stereo audio on 5-pin terminal blocks
MAX. OUTPUT LEVEL:	Audio: 18.5Vpp
BANDWIDTH (-3dB):	>100 kHz
S/N RATIO:	90dB @1kHz
CONTROL:	Output level control:-77 to +6dB, R+/-, L+/- channels
AUDIO THD + NOISE:	0.008%
AUDIO 2d HARMONIC:	0.001%
POWER CONSUMPTION:	12V DC, 89mA
INCLUDED ACCESSORIES:	Power supply
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
Product Weight	0.2kg (0.4lbs) approx
Shipping Dimensions	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
Shipping Weight	0.5kg (1.1lbs) approx

