



kramer

TR-2A

Balanced Stereo Audio Isolation Transformer



The TR-2A is a high-performance isolation transformer for balanced stereo audio signals. It completely isolates devices to eliminate hum, ground loops, and DC offsets that can degrade audio quality

FEATURES

S/N Ratio - -83dB @ $+4\text{dBu}$, 1kHz

External Input & Output Ground Terminals

Grounding Options - DIP-switch selectable

Passive - No power required

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



kramer

TECHNICAL SPECIFICATIONS

INPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block
OUTPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block
MAX. OUTPUT LEVEL:	+26dBu
BANDWIDTH (-3dB):	20Hz to 20kHz
S/N RATIO:	-83dBu @+4dBu/1000Hz
CONTROLS:	DIP-switches to connect to chassis
COUPLING:	Transformer
AUDIO THD + NOISE:	0.025% @+4dBu/1000Hz
INCLUDED ACCESSORIES:	Mounting brackets
Product Dimensions	12.12cm x 7.23cm x 3.07cm (4.77" x 2.85" x 1.21") W, D, H
Product Weight	0.3kg (0.6lbs) approx
Shipping Dimensions	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H
Shipping Weight	0.5kg (1.2lbs) approx

