

## PT-2C

4K60 4:2:0 Extended EDID Processor

| HDMI



PT-2C is an EDID processor for 4K HDMI signals. It allows you to pass or block HDCP, multi-channel audio or deep color signals that may or may not be compatible with the display

### FEATURES

- Max. Resolution - 4K@60Hz (4:2:0)
- Max. Data Rate - 8.91Gbps (2.97Gbps per data channel)
- HDMI Compliance
- Signal Reclocking
- Active Video Signal Source Detection
- Configurable Timeout - For when the input signal is lost



## TECHNICAL SPECIFICATIONS

---

INPUT:	1 HDMI connector
OUTPUT:	1 HDMI connector
PORTS:	1 mini USB
MAX DATA RATE:	10.2Gbps (3.4Gbps per data channel)
CONTROLS:	8 DIP-switches
STANDARDS:	HDMI with Deep Color, x.v.Color™ and 3D; HDCP—works with sources that support HDCP repeater mode
INDICATOR LEDS:	HDMI In, HDMI Out, Power
POWER REQUIREMENTS:	5V DC, 315mA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	–40° to +70°C (–40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
COOLING:	Convection
ENCLOSURE TYPE:	Aluminum
RACK MOUNT:	With optional adapter
FURNITURE MOUNT:	With included rubber feet
VIBRATION:	ISTA 1A in carton (International Safe Transit Association)
COMPLIANCE STANDARDS:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	Power supply, bracket kit
Product Dimensions	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
Product Weight	0.1kg (0.2lbs) approx
Shipping Dimensions	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
Shipping Weight	0.4kg (0.9lbs) approx



