



kramer

BCP-2X

Bulk Dual Mini Coax High-Resolution s-Video
Cable - Plenum Rated



Kramer's BCP-2X is a plenum rated, high resolution, dual mini coaxial cable perfect for routing s-Video signals, also known as Y/C, in professional AV systems

FEATURES

Plenum Rated - The low smoke and fire-resistant properties of plenum rated cable allow it to reside in air return spaces of ceiling, floors, and walls, often saving the cost of installing conduit

Quality Construction - Each mini coax has an industry standard 26AWG center conductor and a dual shield design consisting of copper spiral and aluminum Mylar foil

Numerous Applications - When terminated with RCA connectors, BCP-2X becomes an excellent plenum rated cable for unbalanced stereo audio

Universal Compatibility - Compatible with Kramer's compression connectors as well as typical crimp systems

Length - Available in reels of 76/152/304m (250/500/1000ft)



kramer

TECHNICAL SPECIFICATIONS

CONSTRUCTION	Coax Center Conductor: 26AWG 7/34 tinned copper Dielectric: Foam FEP Shield: (A) 38AWG tinned copper 95% spiral braid. (B) 100% aluminum Mylar foil Coax Jacket Colors: Red, yellow Outer Jacket: Lead free plenum rated PVC Outer Jacket Color: Black with white lettering
DIAMETERS	Center Conductor: 0.48mm (0.019in) Dielectric: 1.83mm (0.072in) Individual Coax: 2.59mm (0.102in) Outside Diameter: 6.1mm (0.240in)
ELECTRICAL	Impedance: 75Ω DC Resistance: 134.5Ω/km (41Ω/1000ft) Capacitance: 16.0pF/ft Velocity of Propagation: 83% Voltage: 150V RMS Temperature: -6° to 75°C (21° to 167°F)
REGULATORY	UL: CL2P CSA: CMP, FT6 NEC: In accordance with article 725 RoHS: In compliance with European directive 2002/95/IEC, issue 13.2.2003
Note:	For best results, keep plenum cable at room temperature for 24 hours before use



CONFIGURATIONS

BCP-2X-250	2 Coax 26 AWG s-Video Plenum Rated Cable
BCP-2X-500	2 Coax 26 AWG s-Video Plenum Rated Cable
BCP-2X-1000	2 Coax 26 AWG s-Video Plenum Rated Cable
