



# kramer

## CP-GM/5BM(M)

15-pin HD to 5 BNC Molded Breakout Cable  
- Plenum Rated

| VGA/UXGA - 15-pin HD



Kramer's CP-GM/5BM (M) series premium quality cables are constructed of plenum 5 mini coax cable terminated with a molded 15-pin HD connector at one end, and 5 BNCs at the other. They offer outstanding durability and high performance for any computer graphic video signal application where a plenum rating is required

### FEATURES

**Quality Construction** - Constructed from flexible, high-quality plenum rated cable containing 5 mini coaxes. BNCs are premium quality true  $75\Omega$

**Plenum Rated** - The low smoke and fire-resistant properties of plenum rated cable allow it to reside in air return spaces of ceiling, floors, and walls, often saving the cost of installing conduit

**Numerous Applications** - Ideal for applications requiring passive breakout from 15-pin to RGBHV. Ideal for routing typical computer video and audio signals in professional AV systems

**Cable Specs** - For detailed specs, see Kramer BCP-5X bulk cable

**Varied Selection of Lengths** - Available in versions of 3.0 to 30.5m (10, 15, 25, 35, 50, 75, 100ft)



## TECHNICAL SPECIFICATIONS

---

Before use:	For best results, keep plenum cable at room temperature for 24 hours before use
Coax Center Conductor:	26 AWG 7/34 tined copper
Coax Jacket Colors:	Red, Green, Blue, Yellow, Black
Dielectric:	Foamed FEP
	.072 inches, 1.83 mm
Outer Jacket Color:	Black w/ white lettering
Outer Jacket:	Lead free plenum rated PVC
Shield:	(A) 95% spiral braid 38 AWG tinned copper. (B) 100% Aluminum/poly foil
Center Conductor:	.019 inches, 0.48 mm
Individual Coax:	.102 inches, 2.59 mm
Outside diameter:	.300 inches, 7.62 mm
Attenuation (db/100ft):	 -5.1 dB @ 100MHz. -7.4 dB @ 200MHz. -11.8 dB @ 400MHz. -21.4 dB @ 1000MHz
Capacitance:	16.0pF per foot
DC resistance:	41Ω per 1000 ft
Impedance:	75Ω
VELOCITY OF PROPAGATION.:	83%
Voltage:	150 Volts RMS
Temperature:	21° to 167° Fahrenheit, -6° to 75° Celsius
C (UL):	CMP
NEC:	In accordance with article 725
RoHS:	Fully Compliant
UL:	CL2P



# kramer

## CONFIGURATIONS

---

CP-GM/5BM-10(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-15(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-25(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-35(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-50(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-75(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable
CP-GM/5BM-100(M)	Molded 15-pin HD (M) to 5 BNC (M) Plenum Breakout Cable

---