



BC-2Sxx/LSHF

Speaker Bulk Cable – Low Smoke & Halogen Free

| Speakers



Kramer's BC-2Sxx/LSHF is a high-quality low-smoke, halogen free twisted pair cable designed for connecting speakers and amplifiers in commercial or residential AV systems

FEATURES

Quality Construction - Rugged and flexible jacket with sequential markings every meter

High Performance - Use anywhere an unshielded stranded pair is suitable

Length - Available in reels of 300m (985ft)



TECHNICAL SPECIFICATIONS

CONSTRUCTION	Conductors: BC-2S12/LSHF 12AWG (65/0.254); BC-2S14/LSHF 14AWG (41/0.254); BC-2S16/LSHF 16AWG (26/30) bare copper Insulation: Polypropylene color coded: red, black Outer Jacket Color: Light gray with blue lettering Outer Jacket: LSHF
DIAMETERS	Center Conductor: BC-2S12/LSHF 2.36mm (0.093in); BC-2S14/LSHF 1.87mm (0.074in); BC-2S16/LSHF 1.478mm (0.058in) bare copper PVC Insulation: BC-2S12/LSHF 3.2mm (0.126in); BC-2S14/LSHF 2.5mm (0.099in); BC-2S16/LSHF 2.0mm (0.079in) Outer Jacket: BC-2S12/LSHF 7.5mm (0.296in); BC-2S14/LSHF 6.6mm (0.260in); BC-2S16/LSHF 5.2mm (0.205in)
ELECTRICAL	DC Resistance: BC-2S12/LSHF 5.64Ω/km (1.7Ω/1000ft); BC-2S14/LSHF 8.9Ω/km (2.7Ω/1000ft); BC-2S16/LSHF 13.7Ω/km (4.17Ω/1000ft) Temperature: -20° to 75°C (-4° to 167°F)
REGULATORY	UL: CM CSA: CM, FT4 RoHS: In compliance with European directive 2002/95/IEC DIN & EU Equivalent: EN 50265-1:1998 EN 50265-2-1:1998 EN 50267-2-1:1998 EN 50267-2-2:1998



CONFIGURATIONS

BC-2S12/LSHF-300M	Speaker Cable 12AWG - Low Smoke & Halogen Free
-------------------	--

BC-2S14/LSHF-300M	Speaker Cable 14AWG - Low Smoke & Halogen Free
-------------------	--
