



VP-439

HDMI, PC and CV to HDMI Classroom
Switcher / Scaler

| HDMI | Ethernet - RJ-45



The VP-439 is a high-performance digital scaler for computer graphics video, composite and HDMI signals, including audio. It up/down scales the selected HDMI, CV or computer graphics video/YPbPr input and outputs it to HDMI on a DVI-I connector

FEATURES

Maximum Resolution - Up to 1080p/WUXGA

HDTV Compatible

HDCP Compliant

Auto Switching - Searches for a valid signal when the input signal is lost

Automatic Input Audio Detection and Selection - Selects embedded audio for HDMI inputs, or analog audio when DVI is detected

Auto-Power Down - If no input signal is detected for 2 to 3 minutes, output is shut down

Analog Audio Inputs - For CV, PC and HDMI

Lip Sync Delay

On-Screen Display (OSD) - For easy setup and adjustment, accessible via the front-panel buttons

Flexible Control Options - Front panel buttons, OSD (on-screen display), Web page, Ethernet, RS-232

Built-in ProcAmp - For convenient adjustment of video parameters, such as brightness, contrast, color, sharpness and hue

Non-Volatile Memory - Saves final settings



TECHNICAL SPECIFICATIONS

| | |
|---------------------------|--|
| INPUTS: | 1 HDMI with unbalanced stereo on a 3.5mm mini jack, 1 PC/HD (RGBHV/YPbPr) on a 15-pin HD connector with unbalanced stereo on a 3.5mm mini jack, 1 composite video on an RCA connector with unbalanced stereo on 2 RCA connectors |
| OUTPUTS: | 1 HDMI on a DVI-I connector with unbalanced stereo on 2 RCA connectors |
| PORTS: | 1 Ethernet on an RJ-45 connector, 1 RS-232 on a 9-pin D-sub connector |
| OUTPUT COLORSPACE: | RGB/YPbPr |
| OUTPUT RESOLUTIONS: | 1080i, 1080p, 576i, 576p, 720p, 1080i, 1080p, WXGA, WSXGA, WUXGA, 1280x800, WXGA+, SXGA+, NATIVE, VGA, SVGA, XGA, SXGA, UXGA, 480i, 480p, 1600x900 |
| OUTPUT REFRESH RATE: | 60Hz for computer graphics resolutions, 50/60Hz for HDTV resolutions |
| PROCESSING DELAY: | 30ms approx |
| CONTROLS: | Front panel buttons, menu-driven OSD control, Web page |
| POWER CONSUMPTION: | 5V DC, 1.1A |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power supply |
| Product Dimensions | 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H |
| Product Weight | 1.0kg (2.2lbs) approx |
| Shipping Dimensions | 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H |
| Shipping Weight | 1.6kg (3.5lbs) approx |



