



VP-553xl

Boardroom Presentation Switcher/Dual Scaler

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45 | HDCP Compliant | HDBaseT



The VP-553xl is a high-performance 6x2 presentation switcher/scaler for HDMI, HDBaseT and analog signals, and a 4x1 USB switcher. The unit has dual, independent, scaled outputs, the first on both HDMI and HDBaseT connectors, and the second on an HDMI connector. Both can take from the six digital inputs: three HDBaseT and three HDMI signals; while the first also includes analog inputs – for two computer graphics signals, two composite video and two analog TP inputs. Analog, digital and embedded audio are supported, and the unit also includes a microphone input and rich DSP features

FEATURES

Pix-Perfect™ Scaling Technology - Kramer's precision pixel mapping and high-quality scaling technology. High-quality 3:2 and 2:2 pull down de-interlacing and full up- and down-scaling of video input signals

HDTV Compatible

HDCP Compliant - The HDCP (High Definition Content Protection) license agreement allows copy-protected data on the HDMI input to pass only to the HDMI outputs

HDBaseT Range - Up to 70m (230ft) using BC-HDKat6a cable

Cable - For optimum range and performance, use the recommended Kramer cables available at www.kramerav.com/product/VP-553xl

Video Inputs - 3 HDMI connectors, 3 HDBaseT on RJ-45 connectors, 2 VGA on 15-pin HD connectors, each with unbalanced stereo audio on 3.5mm connectors; 2 VGA & audio over CAT 5 on RJ-45 connectors; 2 composite video on RCA connectors with unbalanced stereo audio on 3.5mm mini jacks

Scaled Outputs - 2 HDMI & 1 HDBaseT

Output Resolutions - HDTV and computer graphics and 1080p/UXGA with selectable refresh rates

4x1 USB Switcher - Can be set to follow the switching of the video layer or can be used as an independent switcher. 4 USB-B input connectors, 1 USB-A output connector

OSD (On Screen Display) - For easy setup and adjustment, accessible via the IR remote control and via the front panel buttons

Input and Output Audio Level Adjustment

Selectable Microphone Talkover or Mix Modes

Automatic Audio Detection & Selection - On the HDMI input source, default selection is HDMI. If not present, the unit uses the audio from the analog input. Manual audio selection is also available

Audio Inputs - 3 analog HDMI audio, 2 analog PC audio on 3.5mm mini jacks; 2 stereo CV audio on RCA connectors each with individual level controls

Microphone Input - Dynamic or condenser (with 48V phantom voltage)

Audio Outputs - 2 balanced stereo audio on terminal blocks

Multiple Aspect Ratio Selections - Full, overscan, underscan, letterbox & panscan

Built-in ProcAmp - Color, hue, sharpness, noise, contrast & brightness

Front Panel Control - Audio mute, video blanking & freeze frame

Front Panel Lockout

Built-in Web Pages - For easy setup and remote control

Firmware Upgrade - Via Ethernet

Non-Volatile Memory - Saves final settings

Flexible Control Options - Front panel, IR remote with OSD (on-screen display), Ethernet with built-in Web pages & RS-232

Worldwide Power Supply - 100-240V AC



TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUTS: | 3 HDMI connectors (HDMI, HDCP), 2 VGA on 15-pin HD connectors, 2 composite video on RCA connectors, 2 analog TP on RJ-45 connectors, 3 HDBT on RJ-45 connectors, 4 USB-B ports, 3 unbalanced analog audio on 3.5mm mini jacks for HDMI, 2 unbalanced analog audio on 3.5mm mini jacks for PC, 1 Aux in balanced stereo audio on 5-pin terminal block connectors, 2 balanced audio (L and R) RCA connectors for CV |
| OUTPUTS: | 1 HDBT on RJ-45 connector, 2 HDMI connectors (HDMI, HDCP), 1 USB port, 1 monitor out balanced stereo on a 5-pin terminal block connector, 1 line out balanced stereo on a 5-pin terminal block connector |
| OUTPUT RESOLUTIONS: | NATIVE, 640x480@60, 800x600@60, 1024x768@60, 1280x768@60, 1360x768@60, 1280x720@60, 1280x800@60, 1280x1024@60, 1440x900@60, 1400x1050@60, 1680x1050@60, 1600x1200@60, 1920x1080@60, 1920x1200@60, 720x480p@60, 1280x720p@60, 1920x1080i@60, 1920x1080p@60, 720x576p@60, 1280x720p@50, 1920x1080i@50, 1920x1080p@50 |
| CONTROLS: | TP 1, TP 2, CV 1, CV 2, HDBT 1, HDBT 2, HDBT 3, PC 1, PC 2, HDMI 1, HDMI 2, HDMI 3, USB 1, USB 2, USB 3, USB 4 input selector buttons; 2 blank, 2 mute, 2 freeze buttons; menu, enter, menu arrows, reset to XGA/720p, OSD SELECT, 2 RS-232, IR, Ethernet, 2 level and EQ trimmers, line/mic selector switch, cond/dyn selector switch, mono/stereo selector switch, REM for muting audio |
| POWER CONSUMPTION: | 100-240V AC, 43VA max |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power cord, rack "ears", IR remote control |
| OPTIONS: | Kramer BC-HDKat6a cable |
| Product Dimensions | 19" x 11.93 x 2U (43.6cm x 30.30cm x 8.80cm) W, D, H |
| Product Weight | 3.7kg (8.0lbs) approx |
| Shipping Dimensions | 52.60cm x 47.50cm x 18.40cm (20.71" x 18.70" x 7.24") W, D, H |
| Shipping Weight | 5.1kg (11.2lbs) approx |



