



Aspen 3232HD-3G

32x32 3G HD-SDI Router

| 3G HD-SDI - BNC | Ethernet - RJ-45



Aspen 3232HD-3G is a 32x32 matrix switcher for SDI signals of up to 3G SDI. It is easy to operate and control through the network using the intuitive web pages and through RS-232 using a serial controller. Small and lightweight, it is capable of handling the most demanding applications

FEATURES

Max. Data Rate - 3Gbps

HDTV Compatible

Multi-Standard Operation - 3G-SDI - SMPTE 424M, HD-SDI - SMPTE 292M, SDI - SMPTE 259M-C/344M, DVB-ASI

Advanced Equalization & re-clocking Technology - Rebuilds the digital signal to travel longer distances

Supports ANC Data - Embedded audio, teletext, time code, etc

Cable Equalization - Up to 200m for 1.5G HD signals, 155m for 3G signals

Latency - less than one Frame

Versatile Genlocking - Using an analog signal

Optional Redundant Power Supply



TECHNICAL SPECIFICATIONS

Inputs	32 3G SDI: On 75 Ohm BNC connectors
Outputs	32 3G SDI: On 75 Ohm BNC connectors
Ports	10/100 Base-T Ethernet: On an RJ-45 connector RS-232/422 On a 9-pin D-sub connector
Power	AC Input Range: 100-240V, 50-60Hz Consumption 18W
Environmental Conditions	Operating Temperature: 0° - 40°C (32° - 104°F)
MECHANICAL	Dimensions: 19" x 2" x 2U (48.26cm x 5.08cm x 8.89cm) W, D, H Weight: 2.7kg (6 lbs) approx